


# ROTOFAST SNAP ON ANCHORS



The Rotofast Snap On Anchor is an easy to use, two-part fastener system designed for use with most rigid fiberglass core acoustical panels. Whether you are a contractor or just installing the panels yourself, the Rotofast Snap On Anchors are quick and efficient to install. These mechanical panel fasteners require no glue and relatively no time-consuming measurements. The anchors simply install into the back of the panel and allow you to mark where the anchors will mount. Then screw the ratchets to the wall and push the panel into place. It's that easy!

The Rotofast Panel Anchors may be used to fasten rigid fiberglass core panels to drywall/Ceiling. The panel anchor is approximately 2 inches in diameter and less than 1 inch high. The Rotofast Snap On anchors are very secure and have been testing to have a pullout strength exceeding 45 lb. in standard 6 lb./ft<sup>3</sup> fiberglass insulation board. Each substrate (concrete block, wall board, wood) may require different types of fasteners to attach Rotofast Panel Anchors securely. The acoustical panels may contain any rigid fiberglass core (4 to 12 lbs/ft<sup>3</sup>) and be of a 1 to 4 inch thickness.

## Features:

- Quick and efficient to install
- Saves time and money
- For use with rigid fiberglass core acoustical panels
- Works with a range of densities and thicknesses
- Pullout strength exceeding 45 lb. in 6 lb./sq. ft board